

Data sheet

Lifting station Aqualift XL 200 L Duo, SPF 3000-S1



Article information

article number: 11134
EAN code: 4026092071182
Price group: 50

Product advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

General features

Colour	black
Standard	EN 12050-1
Type of wastewater	with sewage
Installation situation	free-standing installation
System type	Duo

Version

Type of system	duo pump
Shut-off valve	Shut-off valve made of polymer
Backflow preventer	integrated
Pressure pipe connection	horizontal

Dimensions

Net weight	61.97 kg
Gross weight	84 kg
Packaging dimension: length	1650 mm
Packaging dimension: width	1150 mm
Packaging dimension: height	890 mm

Tank/drain body

Tank volume	200.00 l
-------------	----------

Pumping device

Pump	SPF 3000-S1
Number of pumps	2
Operating mode	S1
Impeller type	Multi-vane impeller
Free passage	40 mm
Length of mains cable for pump	5 m

Pumping capacity



Control

Control unit	Connect Pro
Operating voltage	400 V
Mains frequency	50/60 Hz
Rated current (max.)	9 9 A
Output power (max.)	6.2 kW
Performance Active mode	3.0 W
Protection class control unit	IP 54
Motor protection	yes (electronically)
Type of fuse required (control unit)	C 16 A / C 20 A
Self-diagnosis system (SDS)	yes
Main switch	yes
Battery buffering	yes
Multi-line display	yes
Second Screen	yes (Wi-Fi)
Log book function	yes
Modbus (GLT or gateway)	yes (RTU)
Potential-free contact	yes (2)
Alarm sensor	yes
Ext. audible alarm	yes
Level measurement instrument	Immersion pipe
Type of level measurement	pneumatic
SonicControl Option	yes
Filling Option	yes
USB interface	no