


Data sheet

Submersible pump Aquadive KTP 300 without float switch, 10 m



Article information

article number: 28740
EAN code: 4026092000908
Price group: 20

Product advantages

Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

General features

Material	Polymer Stainless steel
Standard	EN 12050-2
Type of wastewater	without sewage
Cable length	10 m

Version

Pump control	without float switch
--------------	----------------------

Dimensions

Net weight	4.33 kg
Gross weight	4.69 kg
Length	275 mm
Width	390 mm
Height	216 mm
Packaging dimension: length	260 mm
Packaging dimension: width	260 mm
Packaging dimension: height	260 mm


Tank/drain body

Pressure pipe connection	R 1 "
--------------------------	-------

Pumping device

Pump	KTP 300
Number of pumps	1
Weight, pump	4.33 kg
Connection type	Schuko (earthed contact) 2-pin
Operating voltage	230 V
Mains frequency	50 Hz
Protection class	I
Insulation class	F
Protection class (pump)	IP 68 (3m)
Temperature monitoring	integrated
Max. temperature (permanent) of conveyed material	40 °C
Hot water resistance for a short time (2 min)	80 °C
Max. pumping capacity	10 m ³ /h
Max. pumping height	6 m
Speed	2800 U/min
Power P1	0.34 kW
Power P2	0.21 kW
Operating mode	S1
Type of pump connection cable	H07RN-F 3G 1.5 mm ²
Impeller type	Multi-vane impeller
Free passage	10 mm
Type of fuse required (pump)	C 16 A
Length of mains cable for pump	10 m
Rated current	1,6 A

Pumping capacity



Control

Operating voltage	230 V
Connection type	Schuko (earthed contact) 2-pin