

Data sheet

Lifting station Aqualift L Duo, SPF 1700-S3, 230V



Article information

article number: 28747
EAN code: 4026092112823
Price group: 20

Product advantages

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has a closed pump tank with a screwed-on access cover. The station is controlled by a user-friendly control unit.

General features

Colour	black
Standard	EN 12050-1
Type of wastewater	for wastewater with and without sewage
Installation situation	free-standing installation
Delivery state	installation-ready
System type	Duo

Version

Type of system	duo pump
Installation	Dry installation
Pump control	Control unit
Backflow preventer	integrated

Dimensions

Net weight	0 kg
Gross weight	0 kg
Length	764 mm
Width	864 mm
Height	610 mm
Packaging dimension: length	0 mm
Packaging dimension: width	0 mm
Packaging dimension: height	0 mm

Tank/drain body

Pressure pipe connection (DN)	80
Pressure pipe connection (OD)	90 mm
Connection for manual diaphragm pump (DN)	32
Venting connection (DN)	70
Inlet nominal size (DN)	50
Number of inlets	4
Pumping volume	50 l
Tank volume	120.00 l
Socket version	including spigot and socket

Pumping device

Pump	SPF 1700-S3
Number of pumps	2
Weight, pump	14 kg
Operating voltage	230 V
Protection class	I
Insulation class	F
Protection class (pump)	IP 68 (3m/48h)
Temperature monitoring	integrated
Max. temperature (permanent) of conveyed material	40 °C
Max. pumping capacity	36 m³/h
Max. pumping height	12 m
Speed	2850 U/min
Power P1	1.1 kW
Power P2	1.7 kW
Operating mode	S3 - 15 %
Type of pump connection cable	H07RN-F 3G 1.5 mm²
Impeller type	Multi-vane impeller
Free passage	40 mm
Length of mains cable for pump	5 m
Rated current	7,7 A

Control

Control unit	Connect
Control unit function	With alarm message
Motor protection switch	yes
Alarm sensor	Float switch
Type of level measurement	mechanical
Protection class control unit	IP 54
Mains frequency	50 Hz
Operating voltage	230 V
Length of mains cable for control unit	5 m
Potential-free contact	optional
GSM interface	no
USB interface	no
Log book function	no
Multi-line display	no
Battery buffering	yes
Self-diagnosis system (SDS)	no
Warning equipment version	acoustic and optical signal
Type of fuse required (control unit)	C 10 A