


Data sheet

Submersible pump Aquadive GTF1000 resistant, without float switch, 10 m



Article information

article number: 28760C
EAN code: 4026092093764
Price group: 20

Product advantages

Description

Submersible pump for faecal-free wastewater

General features

Material
Standard
Type of wastewater
Cable length

Polymer Stainless steel
EN 12050-2
without sewage
10 m

Version

Resistant
Pump control

Resistant to waste water containing salt, softener and condensate
without float switch

Dimensions

Net weight
Gross weight
Length
Width
Height
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

9.7 kg
10 kg
195 mm
195 mm
290 mm
379 mm
326 mm
293 mm

Tank/drain body

Pressure pipe connection

R 1 1/4 "

Pumping device

Pump	GTF 1000 resistant
Connection type	coded plug
Operating voltage	230 V
Protection class	I
Insulation class	F
Protection class (pump)	IP 68 (3m)
Max. temperature (permanent) of conveyed material	40 °C
Hot water resistance for a short time (2 min)	80 °C
Max. pumping capacity	14.5 m³/h
Max. pumping height	10 m
Speed	2700 U/min
Power P1	1.3 kW
Power P2	0.75 kW
Operating mode	S1
Type of pump connection cable	H07RN-F 3G 1.5 mm²
Impeller type	Multi-vane impeller
Free passage	10 mm
Type of fuse required (pump)	C 16 A
Length of mains cable for pump	10 m
Rated current	5,6 A

Control

Operating voltage	230 V
Connection type	coded plug